

• **Full strength:**

Acetaldehyde	Acetic Acid	Acetic Anhydride	Acetone
Acrylic Paint	Aluminum Hydroxide	Ammonium Hydroxide	Antifreeze
Aviation Fuel	Automotive Fluids	Barium Hydroxide	BBQ Sauce
Battery Acid	Bleach	Blood	Bodily Fluids
Boric Acid	Brake Fluid	Calcium Hydroxide	Car Wax
Calcium Hypochlorite	Carbon Black	Castor Oil	Chlorine Water
Chloroform	Citric Acid	Clorox (Bleach)	Coolant
Corn Oil	Cottonseed Oil	Cresol	Dairy Products
Degreasers	Detergents	Drilling Fluids	Enamel Paint
Ethylene Glycol	Ethylenediamine	Fabric Softeners	Ferric Chloride
Floor Wax	Formic Acid	Fruit Juice	Fuel Oil
Glycerol	Gorilla Glue	Grape Juice	Hydraulic Fluid
Hydrocarbon Fluids	Ice Cream	Italian Dressing	Juice
Ketchup	Latex Paint	Laundry Detergent	Linseed Oil
Liquid Polymers	Lubricating Oil	Magnesium Hydroxide	Milk
Mineral Oil	Motor Oil	Nitric Acid	Nutella Spread
Octane	Oil	Oil Paint	Olive Oil
Orange Juice	Paint	Paint Thinners	Paraffin
Petroleum Ether	Phenol	Phosphoric Acid	Polymers
Power Steering Fluid	Propylene Glycol	Ranch Dressing	Resins
Salad Dressing	Sauce	Silicone Oil	Softeners
Sodium Bicarbonate	Sodium Bisulfite	Sodium Chloride	Sodium Hydroxide
Solvents	Soup	Soy Bean Oil	Soy Milk
Spray Paint	Sucrose	Synthetic Motor Oil	Syrup
Tomato Sauce	Tannic Acid	Transformer Oil	Transmission Fluid
Turpentine	Urine	Water	Wine
Wood Stain	Xylene		

• **In Acceptable Dilutions:** (Concentrations shown are relevant to substances in industrial use.)

Hydrochloric Acid (45%)

Hypochlorite Solution (18%)

Hydrogen Peroxide (70%)

Peracetic Acid (15%)

Peroxide (70%)

Potassium Hydroxide (45%)

Sulfuric Acid (50%)